

Model No.	AP-3165312	AP-3165322	AP-3165323	AP-3165324	AP-3165342	AP-3165352	
Solution	H42+HDI8901	F33+FH8536H	IMX323+FH8536H	IMX307+NVP2441H	OV4689+FH8538M	IMX326+FH8538M	
Video output mode	AHD/CVI/TVI/CVBS 4 in 1 ; AHD default						
Resolutions	720P	1080P	1080P	1080P(STARLIGHT)	4MP	5MP	
TV System	PAL/ NTSC						
Min Illumination	0.01Lux/ F1.2 @colorful mode, 0.001Lux/ F1.2@B&W mode						
Lens	3.6mm fixed lens						
Night Vision	SMT IR LED: 5MIL*36PCS, IR Distance up to 30 meters						
IR control	ICR Auto Detect (Day&night auto switch)						
IR status	Under 10 Lux by CDS						
Sync System	Internal						
S/N Ratio	≥50dB						
Electronic Shutter	1/25s~1/50,000s , 1/30s~1/60,000s						
OSD Menu	OSD Optional			with OSD			
UTC	with UTC						
WDR		Support					
Noise Reduction	D NR	3D NR	3D NR	D NR	DNR	DNR	DNR
Housing	Metal BULLET						
Rated Voltage	DC12V±10%						
Power consumption	4.0w (IR on)						
Working Environment	Temperature -20° to 70°, Humidity 90%						
Dimension(L*W*H)	170 (W) x77 (H) x56 (D)mm						
Gross Weight	700g						