



- | Model No. | AP-3120312 | AP-3120322 | AP-3120323 | AP-3120324 | AP-3120342 | AP-3120353 | |
|---------------------|---|-------------|----------------|------------------|----------------|----------------|-----|
| Solution | H42+HDI8901 | F33+FH8536H | IMX323+FH8536H | IMX307+NVP2441H | OV4689+FH8538M | SOIK03+FH8538M | |
| Video output mode | AHD/CVI/TVI/CVBS 4 in 1 ; AHD default | | | | | | |
| Resolutions | 720P | 1080P | 1080P | 1080P(Starlight) | 4MP | 5MP | |
| TV System | PAL/ NTSC | | | | | | |
| Min Illumination | 0.01Lux/ F1.2 @colorful mode, 0.001Lux/ F1.2@B&W mode | | | | | | |
| Lens | 3.6mm fixed lens | | | | | | |
| Night Vision | SMT IR LED: 14MIL*18PCS, IR Distance up to 30 meters | | | | | | |
| IR control | ICR Auto Detect (Day&night auto switch) | | | | | | |
| IR status | Under 10 Lux by CDS | | | | | | |
| Sync System | Internal | | | | | | |
| S/N Ratio | ≥50dB | | | | | | |
| Electronic Shutter | 1/25s~1/50,000s , 1/30s~1/60,000s | | | | | | |
| OSD Menu | OSD Optional | | | with OSD | | | |
| UTC | with UTC | | | | | | |
| WDR | | Support | | | | | |
| Noise Reduction | D NR | 3D NR | 3D NR | D NR | DNR | DNR | DNR |
| Housing | Metal BULLET | | | | | | |
| Rated Voltage | DC12V±10% | | | | | | |
| Power consumption | 4.0w (IR on) | | | | | | |
| Working Environment | Temperature -20° to 70°, Humidity 90% | | | | | | |
| Dimension(L*W*H) | 170 (W) x65 (H) x60 (D) mm | | | | | | |
| Gross Weight | 650g | | | | | | |