

Hi3536D H.265 16CH 5MP NVR

MODEL: AP-242116

Front Panel:



Back Panel:



Software interface:



Product highlights:

- Support H.265+/H.265/H.264 coding front end adaptive access.
- Support ONVIF, Highprofile S, Highprofile G, and can be connected to network cameras that comply with ONVIF, RTSP standards made by many major manufacturers.
- Support IPC front-end Intelligence: target count, object left/lost, area detection, line crossing.
- Support AEeye P2P cloud services, through cloud access, cloud monitoring, cloud forwarding to achieve any terminal access to NVR anytime, anywhere.
- Support immediate playback function under preview screen without affecting other channel preview.
- Support for adaptive bit stream preview and playback 4 screen maximum support 1280*720, single screen 2592*1944.
- Provide networked centralized monitoring and management software.

NVR Technical Parameter:

Product Model		AP-242116
Operating System		Embedded LINUX operating system
Video Standard		H.265+/ H.265/H.264
Intelligent Support	IPC support	Various intelligent detection access and linkages such as line crossing, wondering, face, license plate, audio input abnormality, virtual focus and scene change.
Video & Audio Input	Video Input	16CH 5MP H.265+/H.265/H.264 IP Camera
	Bandwidth	40M
	Audio Input	IPC composite stream network audio input
Video & Audio Output	HDMI Output	1CH, HDMI can output audio at the same time
	VGA Output	1CH
	Preview Split	1/4//9/16 screen
Video & Audio Coding	Video Resolution	5MP/4MP/3MP/1080P and below resolution
	Synchronized Playback	4CH
External Ports	Internet	1 x RJ45 10M/100M adaptive Ethernet port
	USB	2 x USB2.0 rear
HDD	HDD Port	1x SATA
	MAX Capacity	up to 8TB
Network Management	Network Protocol	UPnP (Plug & Play), SNMP (Simple Network Management), NTP (Network Timekeeping), SADP (Device Network Search), SMTP (Mail Service), NFS (Access NAS), iSCSI (IP SAN Application), PPPoE (Dial-up Internet access), DHCP (automatically obtain IP address)
P2P Remote Monitoring	AEeye	Supports iPhone, iPad, Android Smart phone
		Supports Windows 7 and above computer client, supports Apple MAC computer client
Power Supply		DC 12V2A (external adapter)
Working Temperature		-10°C-- + 55°C
Working Humidity		10%-90%
Power Consumption		≤10W (without HDD)
Dimensions		Device : 255mm×220mm×43mm , Packing : 358mm×93mm×258mm
Weight (Without HDD)		N.W. : 0.75Kg ; Packing: 1.1Kg
Outside Carton		10 pcs/carton. Dimension : 462mm×365mm×530mm ; Weight : 12Kg
Installation Method		Desktop installation